Swimmingpool Test 3 in 1

Pack content:

1 aluminium container with 50 test strips

Color gradation:

Free chlorine $0 \cdot 0.5 \cdot 1 \cdot 3 \cdot 5 \cdot 10$ ppm Cl_2 Alkalinity $0 \cdot 80 \cdot 120 \cdot 180 \cdot 240$ ppm CaCO_3 pH $6.4 \cdot 6.8 \cdot 7.2 \cdot 7.6 \cdot 8.4$

Additional indications:

- 1. Low pH readings may result when total alkalinity is less than 80 ppm.
- 2. Above 240 ppm the test field for total alkalinity turns blue.
- The classification of values for free chlorine, alkalinity and pH has been done in accordance with limiting values for the USA.

General indications:

Remove only as many test strips as are required. Close the container immediately after removing a strip. Do not touch the test fields.

Hazard warnings:

This test does not contain any hazardous substances that require mandatory labelling.

Instructions for use:

- 1. Dip the test strip with all test fields into swimming pool water for 5 seconds moving back and forth.
- 2. Shake off excess liquid.
- 3. Compare the test field for free chlorine with color scale.
- 4. Wait 30 seconds.
- 5. Compare the test fields for alkalinity and pH with color scale.

Disposal:

Information regarding disposal can be found in the safety data sheet. You can download the SDS from www.mn-net.com/SDS.

Storage:

Avoid exposing the strips to sunlight and moisture. Keep container cool and dry (storage temperature $4-30\,^{\circ}\text{C}$).

If correctly stored, the test strips may be used until the use-by-date printed on the packaging.











CTL SCIENTIFIC SUPPLY CORP. 1016-3 Grand Boulevard, Deer Park, NY 11729

Tel: 631-242-4249

Web: www.ctlscientific.com

Manufacturer: Macherey-Nagel GMbH & CO. KG Rev: 2025-03