

Oil Test Paper

for the rapid determination of oil in water and/or soil

Color reaction:

The light blue paper turns dark blue on contact with hydrocarbons, particularly gasoline, heating oil, lubricating oil, etc.

Method of Application:

a) Determination of oil in water:

Apply a drop of the water to be tested to the test paper or move the paper back and forth a few times in the test solution. In the presence of oil, blue discolorations appear. The intensity and size of the blue spots are indicative of the quantity of oil contained in the test solution. Water that is **free of oil** will neither moisten nor discolor the paper.

b) Determination of oil in soil:

Press the paper against the soil to be tested and rinse thereafter with clear water. In the presence of oil dark blue spots appear against the light blue background. In the presence of larger quantities of oil, the latter will penetrate through the paper, rendering rinsing superfluous.

Limit of sensitivity:

The sensitivity of the test paper is largely dependent upon the solubility of the hydrocarbons. By moving the test paper back and forth a few times at the surface of the water, the following values can be detected:

Substance	Color Reaction	
	lower limit (mg/L of water)	clearly detectable (mg/L of water)
Petroleum (B.P. 40–80 °C)	250	400
Gasoline (high octane)	10	25
Heating oil	5	10
Lubricating oil	1	5

When testing volatile substances, the color reaction must be evaluated immediately, because it fades rapidly.

Product data and ordering information

Type	Qualitative test paper
Presentation	Pack of 100 strips 20x70 mm
Virage	pale blue to dark blue
Limit of sensitivity	Petroleum ether: 250 mg/l (ppm) Gasoline: 10 mg/l (ppm) Fuel oil: 5 mg/l (ppm) Lubricating oil: 1 mg/l (ppm)
REF	90760